

**SYSTEM AND METHOD FOR THE  
MITIGATION OF PARAFFIN WAX  
DEPOSITION FROM CRUDE OIL  
USING ULTRASONIC WAVES**

Patent Application  
of

**Brian F. Towler  
70 Black Elk Trail  
Laramie, Wyoming 82070**

Attorney

**Emery L. Tracy  
Reg. No. 34,081  
P.O. Box 1518  
Boulder, Colorado 80306-1518  
Telephone: 303-443-1143  
Facsimile: 303-443-1415**

Docket No.: W002.PAT-21

SYSTEM AND METHOD FOR THE MITIGATION OF PARAFFIN WAX  
DEPOSITION FROM CRUDE OIL BY USING ULTRASONIC WAVES

1 The present application is a continuation of pending provisional patent  
2 application Serial No. 60/410,472, filed on September 13, 2002, entitled "System and  
3 Method for the Mitigation of Paraffin Wax Deposition From Crude Oil By Using  
4 Ultrasonic Waves".

5

6 BACKGROUND OF THE INVENTION

7 1. Field of the Invention

8 This invention relates generally to system and method for the mitigation of  
9 paraffin was deposition from crude oil and, more particularly, the invention relates to  
10 a system and method for the mitigation of paraffin wax deposition from crude oil by  
11 using ultrasonic waves.

12

13 2. Description of the Prior Art

14 Wax deposition from crude oil is an enormously expensive problem for oil  
15 producers around the world. In the field, the production tubing is often plugged by  
16 paraffin wax which deposits on the walls of the production tubing and surface flow  
17 equipment. The deposition of the paraffin leads to a fall in the production rates of the  
18 oil from that well.

19 The deposition of the paraffin waxes from the reservoir fluid occurs when the  
20 temperature and pressure move below the cloud point of the fluid. The paraffin  
21 deposits start off as a thin film and slowly deposits in the form of crystalline solids,  
22 which collects on the interior of the tubing and flow-lines and slowly chokes off the  
23 production.

24 Basically, paraffin deposits are carbonaceous material, which is not soluble or  
25 dispersible by the crude oil under the prevailing conditions. Paraffins are composed  
26 primarily of alkanes with formulas  $C_{18}H_{38}$  to  $C_{70}H_{172}$ . These are straight chained and  
27 branch chained compounds, and are generally inert and resistant to attack by acids,  
28 bases, and oxidizing agents. Previous research has shown that n-paraffins are more  
29 responsible for this problem. The formation of the deposit depends on the cloud  
30 point, an available surface and or loss of gas or light ends due to a drop in pressure.

1 The precipitation is not uniform; it has peaks at certain points in the tubing and less  
2 deposition at other places.

3 The cloud point temperature is the key factor controlling the paraffin wax  
4 deposition. Paraffinic hydrocarbon liquids form a paraffin or wax solid phase when  
5 the temperature falls below the cloud point, or Wax Appearance Temperature (WAT),  
6 of the oil. As the oil flows up the well-bore, its pressure drops causing solution gas to  
7 liberate. This solution gas which is liberated acts to some degree as a solvent for  
8 waxes. Therefore, the loss of gas increases the cloud point temperature causing more  
9 precipitation and also makes the oil more viscous.

10 Also, as the oil moves upward, it cools since the ground temperature is less  
11 than the reservoir temperature. There is a temperature gradient at the wall and when  
12 the oil temperature reaches the cloud point the precipitation starts. This precipitation  
13 occurs even if the bulk oil temperature is more than the cloud point temperature,  
14 because it is the temperature of the oil at the wall, which plays the most important role  
15 in the precipitation of wax. The wax deposition problem is more prevalent in low  
16 flow rate wells because of the high residence time of oil in the well-bore. The  
17 increased flow time leads to more heat loss, which results in lowering of oil  
18 temperature and leads to wax precipitation and deposition. Well-bore studies have  
19 shown that the temperature profile in the well-bore is a strong function of the flow-  
20 rate. The paraffin wax problem is an example of fluid/solid equilibrium, which is  
21 described as a solution of higher molecular weight hydrocarbons in low molecular  
22 weight hydrocarbons which act as solvents.

23

## 24 SUMMARY

25 The present invention is a method for mitigating the deposition of wax on  
26 production tubing walls. The method comprises positioning at least one ultrasonic  
27 frequency generating device adjacent the production tubing walls and producing at  
28 least one ultrasonic frequency thereby disintegrating the wax and inhibiting the wax  
29 from attaching to the production tubing walls.

30 In addition, the present invention includes a system for mitigating the  
31 deposition of wax on production tubing walls. The system comprises at least one  
32 ultrasonic frequency generating device adjacent the production tubing walls and at  
33 least one ultrasonic frequency generated by the generating device thereby

1 disintegrating the wax and inhibiting the wax from attaching to the production tubing  
2 walls.

#### 3 4 BRIEF DESCRIPTION OF THE DRAWINGS

5 FIG. 1 is a schematic drawing illustrating the system and method for  
6 mitigation of paraffin wax deposition from crude oil using ultrasonic waves,  
7 constructed in accordance with the present invention;

8 FIG. 2 is a schematic drawing illustrating the system and method for  
9 mitigation of paraffin wax deposition from crude oil using ultrasonic waves,  
10 constructed in accordance with the present invention, with the tube in the horizontal  
11 orientation;

12 FIG. 3 is a schematic drawing illustrating the system and method for  
13 mitigation of paraffin wax deposition from crude oil using ultrasonic waves,  
14 constructed in accordance with the present invention, with the tube in the vertical  
15 orientation; and

16 FIG. 4 is a schematic drawing illustrating an experimental setup of the system  
17 and method for mitigation of paraffin wax deposition from crude oil using ultrasonic  
18 waves, constructed in accordance with the present invention, with an ultrasonic water  
19 bath connected to a water cooler pump combination used to circulate water at a fixed  
20 temperature.

#### 21 22 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

23 As illustrated in FIG. 1, the present invention is a system and method,  
24 indicated generally at 10, for mitigating the deposition of wax on production tubing 12  
25 accumulated from crude oil during production by the use of ultrasonic waves. The  
26 system and method of the present invention uses ultrasonic waves to disintegrate the  
27 wax and inhibit the wax from attaching to the walls.

28 The ultrasonic waves or frequencies are generated by at least one device or  
29 sonde 14 attached to the outside of the production tubing 12 at strategic locations  
30 along its length. While three particular frequencies have been identified as the  
31 optimal frequencies of operation, these are only a guide for selection of the desirable  
32 frequencies of operation. In a preferred embodiment, the high frequency is  
33 approximately five hundred (500) KHz and the low frequency is about ten (10) KHz.

1           The first frequency is the characteristic frequency of the production tubing,  
2 designated optimal frequency one (OF1). Using the first frequency, the ultrasonic  
3 waves set the production tubing 12 vibrating thereby inhibiting the wax from  
4 depositing on the wall. The second frequency (optimal frequency two (OF2)) is the  
5 frequency that breaks the wax up into smaller particles by breaking the bonds which  
6 cause the wax molecules to adhere together. The third frequency (optimal frequency  
7 three (OF3)) actually breaks the bonds of the wax molecules so that the long chained  
8 alkanes are broken down into smaller molecules. These smaller molecules will be  
9 more soluble in the oil and so will not precipitate out as wax. Consequently the  
10 ultrasonic wave generator 14 will be broadcasting at all or any of the three frequencies  
11 depending on which of the frequencies are not having the desired effect.

12           In practice, however, these three frequencies would only be a guide for  
13 selection of the desirable frequencies of operation. The present invention includes a  
14 variable frequency device 16 for determining the optimal frequencies in the range  
15 around the three theoretical optimal frequencies. The ultrasonic broadcast device 14  
16 generates all three frequencies, once they have been identified by the variable  
17 frequency device 16.

18           The three frequencies would have three separate effects. As briefly described  
19 above, the OF1 sets the production tubing walls 12 vibrating and hence, inhibits wax  
20 molecules from depositing on the walls. Instead, the wax molecules remain entrained  
21 in the flowing oil and are carried away. The OF2 inhibits the precipitated wax  
22 molecules from adhering together and from adhering to the walls. The OF3 breaks the  
23 unprecipitated long chain wax molecules into smaller molecules and makes the wax  
24 molecules more soluble in the oil thereby lowering the cloud point temperature and  
25 allowing the molecules to remain in solution. The combination of these three effects  
26 greatly reduces the wax deposition so that it is more manageable and removal is  
27 required far less frequently.

28           As illustrated in FIGS. 2 and 3, a paraffin deposition flow system 20 has been  
29 constructed to simulate the deposition of paraffin in the wells. The flow system 20  
30 consists of two concentric tubes with a facility to measure the pressure drop between  
31 the ends of the inner tube, called the test section. The crude oil used to conduct the  
32 experiments is stored in a reservoir having a capacity of ten gallons. The crude can be  
33 pumped into the test section and back into the reservoir. The flow rate is adjusted

1 using a flow meter and a bypass valve. An inclined manometer is used to measure the  
2 pressure drop across the section. The pressure drop is used to determine the pipe  
3 diameter and hence the thickness of the wax deposition. The manometer was inclined  
4 at an angle of thirty-five ( $35^{\circ}$ ) degrees to the horizontal and the manometric fluid is  
5 water. A facility to monitor the temperature in the test section and in the reservoir is  
6 also provided. A blower was required to keep the pump from over heating as the  
7 experiments are run for long periods. A water bath attached to a refrigeration unit is  
8 used to provide cooling for the walls of the inner tube.

9 Water is pumped into the outer annulus and then back into the water bath  
10 maintaining the walls of the test section at the required temperature throughout the  
11 experiment. At the start of each experiment, the manometer is checked to ensure zero  
12 reading and the flow rate adjusted using pump speed and a bypass valve. Manometer  
13 readings are noted at regular intervals until the end of the experiment. At the end of  
14 experiment, all the pumps and coolers are switched off and test section is disassembled.  
15 Paraffin that is deposited in the test section is removed using scrapers and the amount  
16 of paraffin measured using a measuring jar. The ultrasonic frequency generating  
17 equipment is attached to the outside of the tube carrying the flowing oil.

18 The static experimental setup to study the effect of ultrasonic waves on wax  
19 deposition is shown in Fig. 4. It consists of an ultrasonic water bath that was  
20 connected to a water cooler pump combination that was used to circulate the water at  
21 some fixed temperature throughout the duration of the experiment.

22 The foregoing exemplary descriptions and the illustrative preferred  
23 embodiments of the present invention have been explained in the drawings and  
24 described in detail, with varying modifications and alternative embodiments being  
25 taught. While the invention has been so shown, described and illustrated, it should be  
26 understood by those skilled in the art that equivalent changes in form and detail may  
27 be made therein without departing from the true spirit and scope of the invention, and  
28 that the scope of the present invention is to be limited only to the claims except as  
29 precluded by the prior art. Moreover, the invention as disclosed herein, may be  
30 suitably practiced in the absence of the specific elements which are disclosed herein.